

SUPER FINE

Sustainably oriented, EverZinc's distilled zinc powder is produced from **recycled zinc**. Our products are extensively used in the manufacturing of **liquid and powder coatings** and complies with ASTM D520 Type I and Type II (EP).

- Applications :**
- . Zinc primers (silicates, epoxies, polyurethanes...solventborne and waterborne)
 - . Shop primers
 - . Mechanical plating
 - . Sherardizing
 - . Cold galvanizing
 - . Zinc flakes
 - . Thermal spraying

- Packaging :**
- . Metal drums **25-50kg**
 - (UN approved) . Big bags **400-1000kg**

- Shelf Life :**
- . Metal drums **12 months**
 - (Recommended) . Big bags **12 months**

Storage :

Indoor in a dry ventilated location.

To maximize the shelf life and maintain product integrity, do not open the packaging until material is to be used.

Physical data	Standard/Method	Specification
Particle size (x50)	Sympatec	3.6 μ m – 4.7 μ m
Sieve residue at 45 μ m	Brushing	\leq 0.01%
Oil Absorption	ASTM D281/Titration	6,50%

Chemical data	Standard/Method	Type I	Type II (EP)
Total zinc	Calculation	\geq 98.5%	\geq 98.5%
Metallic zinc	Gas evolution	\geq 94%	\geq 94%
Pb	ISO 3549/MPAES	\leq 0.1%	\leq 0.01%
Cd	ISO3549/MPAES	\leq 0.04%	\leq 0.01%
Fe	ISO3549/MPAES	\leq 0.005%	\leq 0.005%

The information contained herein has been compiled to the best of EverZinc's knowledge and is presented without any obligation.

EverZinc Malaysia Sdn Bhd
Plant & Commercial Offices

PLO 376, Jalan Perak Empat,
81700 Pasir Gudang, Johor
Malaysia
Phone: +60 7 254 74 00
Website: www.everzinc.com

EverZinc HQ

Fullbright Tower, 1301 McKinney Street, Ste 1575
Houston, TX 77010
USA

